

Series G, Model B Mechanical Metering Pumps

Configuration Data

Model **G51** **8** **541P**

Output Code ⁽¹⁾

G51	26	GPH @ 60 Hz (82 l/h @ 50 Hz)	... 150	psi (10.0 Bar)
G52	53	GPH @ 60 Hz (167 l/h @ 50 Hz)	.. 150	psi (10.0 Bar)
G53	106	GPH @ 60 Hz (334 l/h @ 50 Hz)	.. 150	psi (10.0 Bar)
G58 ⁽²⁾	---	(418 l/h @ 50 Hz)	(10.0 Bar)
G63	147	GPH @ 60 Hz (464 l/h @ 50 Hz)	.. 100	psi (7.0 Bar)
G68 ⁽²⁾	---	(580 l/h @ 50 Hz)	(7.0 Bar)
G73	300	GPH @ 60 Hz (946 l/h @ 50 Hz)	50 psi (3.5 Bar)
G78 ⁽²⁾	---	(1183 l/h @ 50 Hz)	(3.5 Bar)

Motor

8	3/4 hp, 1-Phase, 60 Hz, 115/230V, 1800 rpm, TEFC, 56C Frame
L	0.55 kW, 3-Phase, 50 Hz, 220/380V, 1500 rpm, TEFC, F165 Flange, 80 Frame
J	3/4 hp, 3-Phase, 60 Hz, 230/460V, 1800 rpm, TEFC, 56C Frame
P	DC Variable Speed Motor, 1 hp, 1-Phase, 120 V, 50/60 Hz
N	No Motor (IEC 80 Frame, F165 Flange)
X	No Motor (56C Frame)

Liquid End


See next page for complete liquid end specifications and selection.



Specifications

Series	Capacity ⁽¹⁾ (per Hour)		Strokes per Minute		Maximum Injection Pressure	Stroke Length (Adjustable) Recommended Minimum	Shipping Weight
	Gallons @ 60 Hz	Liters @50 Hz	60 Hz	50 Hz			
G51	26	82	43	36	150 psi (10 Bar)	0 - 100% (Minimum 10%)	88 lbs (40 kg) ⁽³⁾
G52	53	167	86	72	150 psi (10 Bar)		
G53	106	334	173	144	150 psi (10 Bar)		
G58 ⁽²⁾	----	418	----	180	----- (10 Bar)		
G63	147	464	173	144	100 psi (7 Bar)		
G68 ⁽²⁾	----	580	----	180	----- (7 Bar)		
G73	300	946	173	144	50 psi (3.5 Bar)		
G78 ⁽²⁾	----	1183	----	180	----- (3.5 Bar)		

(1) Outputs are at maximum rated pressure. At reduced pressures add 1% per 25 psi (1.7 Bar)
 (2) Available only with 50 Hz motor
 (3) 106 lbs (48 kg) with stainless steel liquid end



Fred C. Gilbert Co.
 106 Norris Road
 Bakersfield, Ca. 93308
 661-399-9569
 fax 661-393-9654



Configuration Data & Materials of Construction

Drive Assembly	Liquid End No.	Size Code	Materials of Construction					Connections	
			Head / Fittings	Valve Balls	Diaphragm	Valve Seat	Seals	Inch	Metric
G51 ■ - G52 ■ - G53 ■ - G58 ■ -	541P	40	Polypropylene/PVC	Glass	PTFE	PE	Viton®	1/2" NPT F	DN15
	541Q	40	Polypropylene/PVC	Glass	PTFE	PE	Viton®		
	542P	40	PVDF	Ceramic	PTFE	PVDF	PTFE	1/2" NPT F	
	542N	40	PVDF	Ceramic	PTFE	PVDF	PTFE		1/2" BSP F
	547P	40	316 SS	316 SS	PTFE	316 SS	Viton®	1/2" NPT F	
	547N	40	316 SS	316 SS	PTFE	316 SS	Viton®		1/2" BSP F
	548P	40	PVC	Glass	PTFE	PE	Viton®	1/2" NPT F	
	548Q	40	PVC	Glass	PTFE	PE	Viton®		DN15
54PP*	40	PVC	316SS	PTFE	316SS	Viton®	1/2" NPT F		

G63 ■ - G68 ■ -	561P	60	Polypropylene/PVC	PVC	PTFE	PE	Viton®	1" NPT F	DN25
	561Q	60	Polypropylene/PVC	PVC	PTFE	PE	Viton®		
	562P	60	PVDF	Ceramic	PTFE	PVDF	PTFE	1" NPT F	
	562N	60	PVDF	Ceramic	PTFE	PVDF	PTFE		1" BSP F
	567P	60	316 SS	316 SS	PTFE	316 SS	PTFE	1" NPT M	
	567N	60	316 SS	316 SS	PTFE	316 SS	PTFE		1" BSP M
	568P	60	PVC	PVC	PTFE	PE	Viton®	1" NPT F	
	568Q	60	PVC	PVC	PTFE	PE	Viton®		DN25
56PP*	60	PVC	316SS	PTFE	316SS	Viton®	1" NPT M		

G73 ■ - G78 ■ -	581P	80	Polypropylene/PVC	PVC	PTFE	PE	Viton®	1" NPT F	DN25
	581Q	80	Polypropylene/PVC	PVC	PTFE	PE	Viton®		
	582P	80	PVDF	Ceramic	PTFE	PVDF	PTFE	1" NPT F	
	582N	80	PVDF	Ceramic	PTFE	PVDF	PTFE		1" BSP F
	587P	80	316 SS	316 SS	PTFE	316 SS	PTFE	1" NPT M	
	587N	80	316 SS	316 SS	PTFE	316 SS	PTFE		1" BSP M
	588P	80	PVC	PVC	PTFE	PE	Viton®	1" NPT F	
	588Q	80	PVC	PVC	PTFE	PE	Viton®		DN25
58PP*	80	PVC	316SS	PTFE	316SS	Viton®	1" NPT M		

■ See front page for voltage code specifications.

Viton is a registered trademark of E. I. du Pont de Nemours & Co., Inc.

* 5xPP= High Viscosity Liquid Ends

